



LENNERTS
& PARTNER GmbH

Scanner FS5

Quick start guide



Scanner FS5

CONTENT

1	Scope of delivery	2
1.1	Device	2
1.2	Docking station	3
1.3	Handle	3
2	Device specification	4
3	Buttons and ports	5
4	Setup and configuration	6

1 SCOPE OF DELIVERY

1.1 DEVICE

FS5



Power supply



USB/USB-C cable



1.2 DOCKING STATION

Docking station



Power supply



USB/USB-C cable



1.3 HANDLE

Handle



2 DEVICE SPECIFICATION

Temperature range	
Usage	-10°C bis +55°C
Storage	-30°C bis +70°C

Protection classes	
IP65	Complete touch protection, protection from dust, protected against water jets (from any direction)
MIL-STD 810G	Falls from up to 1,2m height

3 BUTTONS AND PORTS



No	Button / Port	No	Button / Port
1	Mikrophone	9	Scan button
2	Speaker (front)	10	Power button
3	Ambient light sensor	11	Camera (back)
4	Camera (front)	12	Speaker (back)
5	Barcode scanner	13	SIM card port (under the cover)
6	Scan button	14	USB-C
7	Volume button (+)	15	Audio output
8	Volume button (-)		

4 SETUP AND CONFIGURATION

After receiving the device it needs to be configured. For this purpose, an employee of LENNERTS & PARTNER GmbH needs to access the scanner via TeamViewer.

Please follow these steps:

1. Turn the device on.
2. Connect the device in the settings to the WIFI.
3. Start the pre-installed TeamViewer application.
4. Send the TeamViewer ID to the support of LENNERTS & PARTNER GmbH (support@lennerts-partner.de).
5. An employee of LENNERTS & PARTNER GmbH will connect each app to the database.